

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT


(10) International Publication Number
WO 2005/049664 A1

(51) International Patent Classification ⁷ :	C08F 10/02	(DE). DRÖGE, Thomas [DE/DE]; Maconring 98a, 67434 Neustadt a. d. W. (DE).
(21) International Application Number:	PCT/EP2004/012108	
(22) International Filing Date: 27 October 2004 (27.10.2004)		
(25) Filing Language:	English	
(26) Publication Language:	English	
(30) Priority Data:		
103 51 262.4 60/525,268	31 October 2003 (31.10.2003) 25 November 2003 (25.11.2003)	DE US
(71) Applicant (for all designated States except US): BASELL POLYOLEFINE GMBH [DE/DE]; Brühler Strasse 60, 50389 Wesseling (DE).		
(72) Inventors; and		
(75) Inventors/Applicants (for US only): GONIOUKH, Andrei [RU/DE]; Am Kapellenbusch 15, 50374 Erftstadt-Liblar (DE). KÖHLER, Gernot [DE/DE]; Johann-Sebastian-Bach Weg 3, 53340 Meckenheim (DE). TEUBER, Theo [DE/DE]; Maarweg 46, 50374 Erftstadt		

Declaration under Rule 4.17:
— *of inventorship (Rule 4.17(iv)) for US only*

[Continued on next page]

(54) Title: CONTINUOUS PREPARATION OF ETHYLENE HOMOPOLYMERS OR COPOLYMERS



(57) **Abstract:** The invention relates to a process for the continuous preparation of ethylene homopolymers or copolymers in the presence of free-radical polymerization initiators and, if desired, molecular weight regulators at from 120°C to 350°C and pressures in the range from 100 to 4000 bar, in which the polymer is separated from unpolymerized ethylene in a high-pressure stage at a pressure of from 100 to 500 bar and at least one low-pressure stage at a pressure of from 1 to 100 bar and the ethylene separated off in the high-pressure stage is separated from remaining monomeric, oligomeric and/or polymeric constituents and recirculated to the inlet of the tube reactor in a high-pressure circuit and the ethylene separated off in the low-pressure stage is separated from remaining monomeric, oligomeric and/or polymeric constituents and recirculated to the inlet of the tube reactor in a low-pressure circuit. The initiator is used as a solution in an isoparaffinic solvent having a boiling point of not more than 160°C and the solvent is separated from the other monomeric, oligomeric and/or polymeric constituents in the low-pressure circuit. The solvent is then, if appropriate after being admixed with fresh solvent, reused for dissolving initiator.